

PI5100

DisplayPort to HDMI Cable with TotalWire™ Technology, Secure Lock

Key Features

- High speed DisplayPort to HDMI cable
- Supports resolutions up to Full HD and WUXGA 1920x1200
- Secure-locking connectors for professional installations
- High purity, tinned OFC copper conductors and 3-layer shielding for optimized transmission quality



Technical Specifications

CONNECTIONS

CONNECTOR MATERIAL	PVC
CONTACT MATERIAL	24 ct. gold-plated
SHIELDING	Yes
CONNECTOR 1	DisplayPort male (20pin)
CONNECTOR 2	HDMI Type A male (19pin)

SIGNAL TRANSMISSION

MAX RESOLUTION	Full HD (1080i/p), 1920x1200 WUXGA
MAX BANDWIDTH	165 MHz
MAX TRANSFER RATE	3.72 Gbps
SUPPORTED STANDARDS	HDCP, CEC
COLOR SPACE	8 bit RGB/YIV, Deep Color, x.vColor™

CABLE

TYPE	Round cable
INNER CONDUCTOR MATERIAL	High purity tinned OFC copper
AWG	AWG28
NUMBER OF SHIELDINGS	3-layer
SHIELDING 1	Aluminium foil (100% sealed)
SHIELDING 2	Aluminium foil (100% sealed)
SHIELDING 3	Braid (100% sealed)
OUTER SHEATH DIAMETER	7.3 mm

CABLE

COLOR	Black
AVAILABLE LENGTHS	3.3 ft. (1m), 6.6 ft. (2m), 10 ft. (3m)
WARRANTY	TotalWire™ Lifetime Limited Warranty