



[View product details](#)



The **PM-CT103-U-H** provides a cost effective and easy to install solution for schools, conference rooms, auditoriums, churches, and more. Enable the connection of HDMI source to HDBaseT display with 3.5mm audio out jack and RS232.

## Specifications

### Connections

Inputs	2x HDMI   1x 3Pin PNX Terminal Block (for Power)   1x 3Pin PNX Terminal Block (for RS-232)   1x 3.5mm Stereo Jack
Outputs	1x CAT connector

### Audio & Video

Video Resolutions	Up to Ultra HD 4K 4096 x 2160 @ 24/25/30Hz (RGB/YCbCr 4:4:4 8 bits, YCbCr 4:2:2 8/10/12 bits)
Date Transfer Rate	3.4 Gbps/ch, Total 10.2 Gbps Max

### Standards & Compliance

Standards	DVI 1.0   HDMI 1.4b   HDCP 1.4
Compliance	Trade Agreements Act (TAA)

### Power

Power Supply	DC+12V
Power Consumption	4W Max

### Environmental

Operating Temperature	32°F ~ 117°F (0°C ~ 47°C)   Up to 90%, non-condensing
Storage Temperature	-40°F ~ 158°F (-40°C ~ 70°C)   Up to 90%, non-condensing

### Enclosure

Type	2 Gang Decora style
------	---------------------

	Product	Shipping
Dimensions	3.6" x 4.24" x 2.24" (91.44 x 107.95 x 57.15 mm)	TBD
Weight	1.0 lbs (0.46 Kg)	TBD

### Warranty

Parts and Labor	3 years
-----------------	---------