HTE III Tx/Rx 4K HDMI over HDBaseT Extension System





The HTE III Tx/Rx is a premium HDMI 2.0 HDBaseT extension system for Ultra HD/4K and HDR formats. The HTE III Tx/Rx supports 4K@60Hz with 4:4:4 chroma sampling, as well as HDMI data rates up to 18 Gbps with HDCP 2.2 compliance.

Individual units also available: HTE III Transmitter and HTE III Receiver

Key Features

- Supports resolutions up to 4K@60Hz (4:4:4)
- Supports HDR (High Dynamic Range) formats
- HDCP 2.2 compliant
- Extends HDMI up to 230 ft. (70m) at Ultra HD/4K and up to 330 ft. (100m) at 1080p
- Précis codec- visually lossless signal transmission
- High bandwidth support up to 18 Gbps
- Supports BT.2020 color representation
- Bi-directional PoE (Power over Ethernet)
- Bi-directional RS232, IR & Ethernet extension
- CEC pass-through

Hardware

AUDIO	LPCM 2/5.1/7.1 Ch, Dolby Digital+, Dolby TrueHD, Dolby Digital, Dolby Atmos, DTS:X, DTS-HD Master Audio, DTS 5.1
INPUT SIGNAL TYPE(S)	TX: 1 x HDMI Type A [19-pin female]; 1 x Firmware [Mini USB] RX: 1 x HDBaseT [RJ45]; 1 x Firmware [Mini USB]
OUTPUT SIGNAL TYPE(S)	TX: 1 x HDBaseT [RJ45] RX: 1 x HDMI Type A [19-pin female]

Performance

SUPPORTED DISTANCE	up to 230 ft. (70m) at Ultra HD/4K and up to 330 ft. (100m) at 1080p
SUPPORTED RESOLUTIONS	Ultra HD/4K up to 4096 x 2160 @50/60Hz (RGB 4:4:4, YCbCr 4:4:4, 4:2:2, 4:2:0)
VIDEO BANDWIDTH	18 Gbps
COMPLIANCE	HDMI 2.0, HDCP 2.2
RS-232	1 x RS232 [Phoenix connector]
IR EXTENSION	1 x IR input [3.5mm stereo mini-jack]; 1 x IR output [3.5mm stereo mini-jack]
POWER CONSUMPTION	24W (max)
POWER SUPPLY	DC 24V/1A (US/EU standard, CE/FCC/UL certified)





HTE III Tx/Rx 4K

4K HDMI over HDBaseT Extension System

OPERATING TEMPERATURE $32^{\circ} \sim 117^{\circ} \text{ F } (0^{\circ} \text{ to } 47^{\circ} \text{ C})$ STORAGE TEMPERATURE $-4^{\circ} \sim 140^{\circ} \text{ F } (-20^{\circ} \text{ to } 60^{\circ} \text{ C})$ RELATIVE HUMIDITY $0 \sim 90\%$ non-condensing
MTBF 50,000 hours

Enclosure

RACK MOUNTING OPTION Standard 19-inch rack-mountable design

PRODUCT DIMENSIONS 7.2" x 3.5" x 0.7" (183 x 88 x 18mm)

PRODUCT WEIGHT 1.0 lbs. (0.45 kg)

Warranty

WARRANTY Limited Warranty (3-Years)