



The HX-4400-U provides switching of up to four (4) HDMI inputs and outputs with support for Ultra HD/4K signals, multiple control options, and advanced EDID management.

## Key Features

- 4x4 HDMI Matrix Switching
- Supports resolutions up to 4K@60Hz (YCbCr 4:2:0)
- Supports full 3D & 48-Bit Deep Color
- HDCP Compliant
- EDID emulation and selectable presets
- Control via front panel display, RS-232, and LAN
- Compatible with third party control devices including AMX, Extron, Vista, and Crestron
- Field-upgradeable firmware

## Technical Specifications

INPUTS	4 HDMI
OUTPUTS	4 HDMI
PC RESOLUTION	Up to 1920 x 1200 @ 60Hz
HDTV RESOLUTION	Up to Ultra HD 4K 4096 x 2160 @24/25/30Hz (RGB/YCbCr 4:4:4 8 bits, YCbCr 4:2:2 8/10/12 bits) 4096 x 2160 @50/60Hz (YCbCr 4:2:0 8 bits)
DATA RATE	10.2 Gbps
OPERATING TEMPERATURE	32° ~ 117° F (0° to 47° C)
STORAGE TEMPERATURE	- 40° ~ 158° F (-40° to 70° C)
HUMIDITY	0 ~ 90% non-condensing
MTBF	95,000 hours
HDMI VERSION	HDMI 1.4
COMPLIANCE	Yes, HDCP 2.0
ACCESSORIES	DC +12V 5.0A (power supply)
DIMENSIONS (W x D x H)	19" x 8.0" x 1.75" in 482.6 x 203.2 x 44.45 mm
WEIGHT	6.7 lbs (3.04 kg)

