PM-FR101-U-RF 4K HDMI over 1 LC Fiber Receiver for RF4-U Extension Center



The PM-FR102-U-RF is a PureMedia™ Fiber Optic extender receiver designed for use with the RF4-U Rack-Mount Extension Center. The PM-FR101-U-RF offers powerful and reliable long-distance extension of Ultra HD/4K video, embedded and analog stereo audio, as well as control signals up to 32,808 ft. (10 km) over a single-mode fiber optic cable.

Key Features

- Extends uncompressed digital video, audio, and control signals over fiber
- Supports resolutions up to Ultra HD/4K
 -10 km. (32,800 ft.) over single-mode fiber
 - -500 m. (1,650 ft.) over multi-mode fiber
- HDCP compliant
- · RS-232 control
- Compatible with the PureMedia[™] matrix switcher fiber outputs (PM-FOS4-U)
- · Compatible with DVI display devices (adapter required)

Technical Specifications

INPUT SIGNAL Fiber Optical Output (> -10dbm (after 32,88ft (10km) transmission))

OUTPUT SIGNAL DVI / HDMI (TMDS), 3.5mm stereo audio (> 4db (after 32,88ft (10km) transmission))

DATA RATE 3.4 Gbps/ch, Total 10.2 Gbps Max

SUPPORTED RESOLUTIONS Up to 3840 x 2160 @24/25/30Hz (RGB 4:4:4, YCbCr 4:4:4, 4:2:2, 4:2:0)

MAX. DISTANCE Single Mode Fiber: 1920 x 1200 @ 60Hz or at 1080p, Ultra HD 4K : 32,808 ft (10km)

Multi Mode Fiber: 1920 x 1200 @ 60Hz or at 1080p, Ultra HD 4K: 1,650 ft (500m)

CONNECTOR TYPE DVI 29P/HDMI 19P Female (x 1)

3.5mm Stereo Jack

1 LC Optical Connector

3P /3.5MM Terminal Block (for Power)
3P /3.5MM Terminal Block (for RS-232)

Mini USB (for firmware update)

SUPPORTED FORMATS DVI 1.0, HDMI 1.4b, HDCP 2.0

POWER CONSUMPTION DC +12V, 4Watts Max

DIMENSIONS(W X D X H) 5.31" x 1.31" x 4.5" (134.93 x 33.33 x 114.3 mm)

WEIGHT 0.5 lbs (226.79g)