


# VIP-200H II Tx/Rx HDMI & USB/KM over IP Extension System



VIP-200HII Rx

VIP-200HII Tx

The **VIP-200H II** HDMI & USB/KM over IP Extension System offers 1080p signal distribution over the network with enhanced features including video wall processing, built-in scaling functionality, and faster switching speeds. Local and remote units can be connected together for point-to-point extension over distances up to 492 ft (150 meters), as well as a point-to-many, many to point, matrix connectivity and up to an 8x8 video wall using the VPX IP Video Management Software.

## Key Features

- Full HD/1080p@60Hz support
- HDCP 1.4 compliant
- Video wall processing (up to 8x8 configuration)
- Built-in scaler (Rx) - pass through or lock output resolutions
- Rs-232 extension/steerable distribution
- USB 2.0 Keyboard/Mouse Extension
- Audio insertion and extraction
- Bi-directional RS-232 and IR control
- Loop-out on transmitter (encoder)
- Point to point, Distribution, Switching, and Matrix systems
- Compatible with VPX IP Video Management Software

## Technical Specification

<b>SUPPORTED DISTANCE</b>	Up to 492ft (150m)
<b>SUPPORTED RESOLUTIONS</b>	Up to 1080p, 1920x1200@60Hz
<b>COMPLIANCE</b>	HDCP 1.4
<b>SUPPORTED AUDIO FORMATS</b>	Up to 7.1 LPCM 192Khz / Dolby True HD / DTS-HD Master Audio/ Dolby Atmos / DTS:X
<b>CONNECTOR TYPE/S</b>	Inputs: (1) HDMI Type A (1) 3.5mm Stereo Phone Jack (line-in) (1) USB 2.0 Type B (1) RS-232 DB9 Female  Outputs: (1) HDMI Type A (1) 3.5mm Stereo Phone Jack (line-out) (1) Gigabit RJ45
<b>IR RECEIVER (INTERNAL)</b>	20-60Khz/ ±45°/5M
<b>IR EMITTER (EXTERNAL)</b>	3.5mm Stereo Phono Jack 20-60Khz/ ±45°/5M
<b>POWER COSUMPTION</b>	1350mA (Typical)
<b>POWER SUPPLY</b>	DC 5V 2000mA
<b>DIMENSIONS (WxDxH)</b>	5.51" x 4.92" x 1.18"
<b>WEIGHT</b>	0.84 lbs.